



Feature

- Sweep performance to 1 GHz
- Dual bonding
- Application temperature - 40°C - 75°C
- Trishield and quadshield are available
- Flooding compound available
- Messenger wire with different breaking strength options
- UL grade available, contact us for details
- LSZH Jacket option available
- ISO9001 Certified Manufacturing Plant
- Other options are available, please ask our sales representative for detail

Coaxial Cable RG58



Specifications

Model		CU5890BV
Construction	Inner Conductor	Stranded Copper Wire
	Braid Coverage	90%
	Center Conductor	19 x 0.18 mm
	Solid PE Insulation	2.95 mm
	TIN - Copper Braiding	16 x 6 x 0.12 mm
	PVC - Jacket	5.00 mm
Electric Specifications	Inner Conductor Resistance	35 Ω / km
	Outer Conductor Resistance	20 Ω / km
	Loop Resistance	53
	Nominal Capacitance	10 μf
	Impedance	50 Ω±2
	Propagation Velocity Ratio	66% Nominal
Packing Size	100 Yards Reel / 4 Reels in a Carton	26 x 10 x 7.2 cm / 27x 27 x 28.5cm
	Gross Weight	16 kg
	Net Weight	15 kg
	200 Yards Reel / 2 Reels in a Carton	26 x 10 x 13 cm / 27x 27 x 28.5cm
	Gross Weight	16 kg
	Net Weight	15 kg

Frequency MHz	50	100	200	550	750	800	1000
Nominal dB / 100m	10.30	14.78	21.42	38.26	46.12	48.07	54.96

Specifications subject to change without notice.

EIGHT LIMITED

No.18, 4/F, Thriving Industrial Centre, 26-38 Sha Tsui Road, Tsuen Wan, N.T., Hong Kong
Tel: (852) 2413 2222 Fax: (852) 2411 3000 Email: info@eightgroup.com



Visit us at Website
<http://www.eightgroup.com>