

Clarigo, clearly better.

308 Portable Two-Way Radio

- · Channel Voice Prompt
- · PTT-ID Encode
- · Scan / Priority Scan
- · VOX Operation
- · Cable Clone

Applications:

Chain hotels, Restaurants, Retail management, Public relations activities and other industry and services.



Clarigo 308 Portable Two-Way Radio Technical Specifications



Main Features

PC Programming Cable Clone English Channel Prompt 9 Squelch Levels Scan/Priority Scan Busy Channel Lockout DTMF Encode/PTT-ID **Battery Save** Frequency Reverse VOX operation **VOX Sensitive Setting** VOX Delay Setting Time Out Timer Squelch Tail Elimination **Emergency Button** Low Battery Alert Monitoring Bandwidth Selectable Power H/L Selectable Repeater Support

Technical Specification

General Specification		
Frequency Range#	UHF 403~470MHz	
Channel Capacity	16	
CTCSS/DCS	50/105	
Channel Spacing	12.5KHz	
Power Supply	DC 7.4V	
Operation Temperature	-20℃~+50℃	
Battery Type/Capacity	Li-polymer / 1400mAh	
Battery Life (5 / 5 / 90 Duty Cycle)	11 hrs	
Dimension (H x W x T)	117×57×32mm	
Weight (Include battery and antenna) 190g		

Receiver

Sensitivity (12 dB SINAD)	≤-119dBm(0.25µV)	
Adjacent Ch Selectivity	≥60dB@12.5KHz	
Hum and Noise	≥35dB@12.5KHz	
Blocking	≥85dB	
Audio Distortion	≤5%	
Audio Power Output	500mW@8Ω	

Transmitter

RF Power Output	UHF H:4W / L:1W
Frequency Stability	±2.5 PPM
FM hum and Noise	≥35dB@12.5KHz
Modulation Limited	≤±2.5KHz@12.5KHz
Adjacent Ch Power	60dBc
Modulation Character	±3dB
Spurious and Harmonics	≤7.5µW
Audio Distortion	≤5%

#Frequency Availability is limited by National laws and regulations.

Above specifications are all typical configuration values,
they may be subject to variations without notice

Standard Accessory







Charger Base



1400mAh Li-ion Battery



Belt Clip

Dealer Stamp:



Antenna



Hand Strap

Optional Accessory



PC Programming Cable



Clone Cable



PTT Earpiece

(For reference only)